

Features and Specifications	Model						
	DRX300s	DRX500s	DRX200	DRX300	DRX4C	DRX4C2	DRX4
Maximum Capacity (g)	300	500	200	300	300	300	100
Readability(d)	0.001	0.001	0.001	0.001	0.001	0.001	0.001
Repeatability(g)	0.001	0.001	0.001	0.001	0.001	0.001	0.001
Linearity (g)	+/- 0.002	+/- 0.002	+/- 0.002	+/- 0.002	+/- 0.002	+/- 0.002	+/- 0.002
Stabilization time	Approx. 3s	Approx. 3s	Approx. 3s	Approx. 3s	Approx. 3s	Approx. 3s	Approx. 3s
Calibration	Auto internal	Auto internal	Auto internal	Auto internal	External wt.	External wt.	External wt.
Tare Range (g)	-300	-500	-200	-300	-300	-300	-100
Accuracy Class	II	II	II	II	II	II	II
Pan Dimension	120 mm	120 mm	120 mm	120 mm	116 mm	116 mm	116 mm
Scale Dimensions	216 x 345 x 90 mm	216 x 345 x 90 mm	216 x 345 x 90 mm	216 x 345 x 90 mm	235 x 245 x 80 mm	235 x 245 x 80 mm	235 x 245 x 80 mm
Operating Temperature	+18C to +33C	+18C to +33C	+18C to +33C	+18C to +33C	+15 to +30C	+15 to +30C	+15 to +30C
RS232 Port	Bidirectional	Bidirectional	Bidirectional	Bidirectional	Bidirectional	Bidirectional	Bidirectional
PS2 Keyboard Port	Standard	Standard	Standard	Standard			
RJ45 Network Port	Optional	Optional					
Database Capacity	10,000	10,000			3,000		
Display type	Graphic 240 x 64 pixels	Graphic 240 x 64 pixels	Graphic 240 x 64 pixels	Graphic 240 x 64 pixels	Large LCD	Large LCD	Large LCD
Sealed Keypad	•	•	•	•	•	•	•
NTEP Approved	•	•	•	•	•	•	•
Counting Transaction Printing	•	•	•	•	•	•	
Onscreen Instructions	•	•	•	•			
Advanced Pill Counting Accuracy Feature	•	•	•	•			
Deviation Warning	•	•	•	•			
Remaining to Fill Display	•	•	•	•			
Navigation Keys	•	•	•	•			
Ingredient Labeling	•	•	•	•			
Filling Meter	•	•	•	•			
Recipe Archiving	•	•	•	•			
Recipe Printing	•	•	•	•			
Laser Barcode Scanner	•	•			•		
RX Verification	•	•			•		
NDC Data Entry Reminder	•	•					
Drug Name Labeling	•	•					
LOT Number Labeling	•	•					